



HOUSEMATE / FARMMATE

High pressure systems

Single and twin impeller shallow well jet pumps. Excellent self priming with high pressure for larger household requirements or rural applications. Cast iron body with stainless steel shaft and Noryl internals.

CTJ 100 / 120

Capable of flows to 70 LPM. Normally equipped with an electronic controller for constant flow and dry run protection.



CTJ 150 / 200 / 300

For long distance high head water delivery, can be equipped with pump mounted 24 litre tank or larger base models.



Model Guide	H.P.	K.W.	Flow	20PSI 140KPA	30PSI 210KPA	40PSI 275KPA	50PSI 345KPA	60PSI 410KPA	70PSI 480KPA	80PSI 555KPA	90PSI 630KPA	User
CTJ100	1.0	.75	GPH	765	700	660	448	238	-	-	-	
			LPM	58	53	50	34	18	-	-	-	
CTJ120	1.2	.90	GPH	924	858	765	475	277	105	-	-	
			LPM	70	65	58	36	21	8	-	-	
CTJ150	1.5	1.1	GPH	-	-	-	1056	885	660	436	-	NON-HOUSE USE
			LPM	-	-	-	80	67	50	33	-	
CTJ200	2.0	1.5	GPH	-	-	-	-	1321	977	555	-	
			LPM	-	-	-	-	100	74	42	-	
CTJ300	3.0	2.2	GPH	-	-	-	-	1585	1215	766	132	
			LPM	-	-	-	-	120	92	58	10	