



# WATERMATE

## Centrifugal pump systems

Single impeller, metal body, centrifugal pumps with high efficiencies. These pumps operate on suction lifts up to 8M, with minimal reduction in performance. Rugged in construction with Noryl, brass or stainless steel impellers depending on model, they provide high heads/medium flows, or medium head/high flow. Smaller units make ideal household supply pumps, while others excel in water transfer, sprinkler operation and dairy washdown.



**CTM 50/100/150/200  
SCM100**

Up to 1.5kW with brass impellers in 1.1 / 1.5kW sizes. Versatile range of 4 models. (SCM100 Brass Impeller).



**SDK100**

Open brass impeller suitable for pumping of light waste, such as from secondary septic tanks.



**CTC100**

Open impeller with high flows using only .75kW. An efficient water transfer unit.

**SSM50 / 100**

All 304 grade stainless steel suits saline and slightly corrosive liquids and can be set up for automatic pressure system application.



**SPM200**

1.5kW in medium head/flow, ideal for small irrigation from shallow well supply.



**SPLI-300(T)**

2.2kW in single or 3 phase. Big flows for dairy washdown or irrigation.



Model	H.P.	K.W.	Flow	15PSI 100KPA	20PSI 140KPA	30PSI 210KPA	40PSI 275KPA	50PSI 345KPA	60PSI 410KPA	70PSI 480KPA
CTM50	.50	.37	GPH	-	925	-	-	-	-	-
			LPM	-	70	-	-	-	-	-
CTM100	1.0	.75	GPH	-	-	1320	790	-	-	-
			LPM	-	-	100	60	-	-	-
CTM150	1.5	1.1	GPH	-	-	-	-	1055	-	-
			LPM	-	-	-	-	80	-	-
CTM200	2.0	1.5	GPH	-	-	-	-	1782	990	-
			LPM	-	-	-	-	135	75	-
SCM100	1.0	.75	GPH	1350	1250	990	225	-	-	-
			LPM	105	95	75	55	-	-	-
SDK100	1.0	.75	GPH	528	-	-	-	-	-	-
			LPM	40	-	-	-	-	-	-
CTC100	1.0	.75	GPH	3170	1980	-	-	-	-	-
			LPM	240	150	-	-	-	-	-
SSM50	.50	.37	GPH	1255	790	-	-	-	-	-
			LPM	95	60	-	-	-	-	-
SSM100	1.0	.75	GPH	1980	1740	895	-	-	-	-
			LPM	150	132	68	-	-	-	-
SPM200	2.0	.5	GPH	-	4360	3560	2375	-	-	-
			LPM	-	330	270	180	-	-	-
SPLI-300	3.0	2.2	GPH	-	5940	4555	2905	790	-	-
			LPM	-	450	345	220	60	-	-

\* OPTIONAL CONTROLS AVAILABLE